



Main Feature:

2MP realtime fix-lens POE Bullet camera with audio

1. resolution: 1920*1080, frame rate: 30fps
2. lens: 3.6mm fixed lens
3. 36 pieces LED light, IR 25-35 meters, IP66
4. DC12V & POE with RJ45 Port , Reset Port
5. **POE: 802.3af , Transmission distance <100m**
6. Phone Support: iPhone, iPad, Android ,System support: Windows ,Mac
- 7.Item Size: 145mm*62mm*98mm
- 8:Item Weight:500g, Package Weight: 0.75kgs
- 9:With Audio
- 10: With reset port

Specification:

Model	E-2MP001POE	
Signal System	Progressive image scan	
Scanning System	16:9 Progressive	
Image Sensor	1.2.7"-Megapixels CMOS	
Sync. System	Internal	
Effective Pixels No.	1920(H) x1080(W)	
Video Output Level	1.0Vp-p (BNC 75Ω composite)	

Lens	Megapixel Lens 3.6mm	
IR LED & Visible Range	IR LED 36pcs Φ 5mm (850nm/60°), Max. 25-35m	
Day & Night System	Mechanical ICR	
Min. Illumination	0.05Lux(Color) / 0 Lux IR On	
Brightness	Auto/Manual	
Contrast	Auto/Manual	
Plug&Play	pnp	
Heatbeat Message	Yes	
Compression	H.264/MJPEG	
Frame Rate	1920x1080 1-30fps ,1280x720 1-30fps	
Resolution	1920x1080,1280x720	
Code Stream	128Kbps~8Mbps, VBR/CBR	
Audio	N/A	
Protocol	HTTP, TCP/IP, UDP, SMTP, DDNS, DNS, SNTP, DHCP, FTP, RTP, RTSP, UPNP, ONVIF	
DDNS	Yes	
LAN Interface	Ethernet 10/100 base-T, RJ45 x1	
System Support	Windows ,Mac	
POE	POE: 802.3a/f , Transmission distance <100m	
User Access Setup	Yes	
After Event Process	Upload JPEG via FTP, Email or specified alarm center	
ONVIF Standard Access	ONVIF V2.0	
Motion Detection	Yes, Support Multiple Setting Areas	
Browser	Internet Explorer 6.0 or Above,Chrome,Firefox	
System Upgrade	Yes, Firmware upgrade	
PTZ Control	Not Applicable for Fixed Cameras	
Power	DC12V ,0.5A	
IP Rating	IP66	