

E-003I Series



PC,Smart Phone,E-mail/FTP receiving alarm information

MP Lens

H.264 Compression type

IP64,Indoor Camera

Motion Detection

Feature:

*Indoor IR IP Vehicle Heavy-Duty Camera

* 1.0/2.0 Mega Pixel 720P/1080P ,1280X720P/1920X1080P

* Video Compression: H.264 Main Profile; AVI Baseline

* Main Stream: HD 1920*1080P 1-25fps

*H.264 Compression Plug & Play,P2P Support Mobile Remote Viewing

*Support ONVIF2.0/2.2/2.3/2.4

*18pcs IR LED, IR distance: 10m-15m

*Megapixel Lens: 2.8mm/3.6mm /6mm/8mm

* Support RTSP Compatible with AVI Media Player

* Onvif Compliant, Support Milestone/Axxon/NUUO/Geovision NVR/Software

*Smart Phone Support: iPhone, iPad, Android

*Language:Arabic,Czech,English,Finnish,Greek,Indonesian,Italian,,Japanese,Portuguese, Russian,Thai,T-Chinese,S-Chinese,Turkish,Bulgarian,Farsi,French,German,Hebrew, Hungarian,Polish,Romanian,Spanish,Swedish

Specification:

Model	E-003I	E-003IH
Signal System	Progressive image scan	
Scanning System	16:9 Progressive	
Image Sensor	1/4",1-Megapixels Sony CMOS	1/2.8",2-Megapixels Sony CMOS
Sync. System	Internal	
Effective Pixels No.	1280(H) x720(W)	1920(H) x1080(W), 1280(H) x720(W)
Video Output Level	1.0Vp-p (BNC 75Ω composite)	
Lens	Megapixel fixed Lens 2.8mm/3.6mm/6mm	
IR LED & Visible Range	IR LED 18pcs Φ5mm (850nm/60°), Max.10-15m	
Day & Night System	Mechanical ICR	
Min. Illumination	0.5Lux(Color) / 0 Lux IR On	
Brightness	Auto/Manual	
Contrast	Auto/Manual	
Mirror	Yes	
Heatbeat Message	Yes	
Compression	H.264/MJPEG	
Frame Rate	1280x720 1-25fps	1920x1080 1-25fps,1280x720 1-25fps
Resolution	1280x720	1920x1080, 1280x720
Code Stream	128Kbps~8Mbps, VBR/CBR	
Audio	N/A (Optional)	
Protocol	HTTP, TCP/IP, UDP, SMTP, DDNS, DNS, SNTP, DHCP, FTP, RTP, RTSP, UPNP, ONVIF	
DDNS	Yes	
LAN Interface	Ethernet 10/100 base-T, RJ45 x1	
Support P.o.E.	POE: 802.3a/f , Transmission distance <100m (Optional)	

WIFI (802.11b/g/n)	No
User Access Setup	Yes
After Event Process	Upload JPEG via FTP, Email or specified alarm center
ONVIF Standard Access	ONVIF V2.0/V.2.2/V.2.3/V2.4
Motion Detection	Yes, Support Multiple Setting Areas
Browser	Internet Explorer 6.0 or Above
System Upgrade	Yes, Firmware upgrade
PTZ Control	Not Applicable for Fixed Cameras
Power	DC12V, 0.5A
Dimension	85mm(L)x50mm(W)x45mm(H)
Weight	0.35kgs
IP Rating	IP64